

Package: gravmagsubs (via r-universe)

October 8, 2024

Type Package

Title Gravitational and Magnetic Attraction of 3-D Vertical
Rectangular Prisms

Version 1.0.1

Description Computes the gravitational and magnetic anomalies
generated by 3-D vertical rectangular prisms at specific
observation points using the method of Plouff (1976)
<[doi:10.1190/1.1440645](https://doi.org/10.1190/1.1440645)>.

License CC0

URL <https://code.usgs.gov/gmegsc/gravmagsubs>

Imports Rcpp (>= 1.0.5)

LinkingTo Rcpp

SystemRequirements GNU make

Suggests knitr, rmarkdown, fields, ggplot2, gridExtra, scales,
scatterplot3d

VignetteBuilder knitr

NeedsCompilation yes

Author C. Cronkite-Ratcliff [aut, cre]
(<<https://orcid.org/0000-0001-5485-3832>>), G. Phelps [aut]
(<<https://orcid.org/0000-0003-1958-2736>>), D. Scheirer [aut]
(<<https://orcid.org/0000-0001-8015-7072>>)

Maintainer C. Cronkite-Ratcliff <ccronkite-ratcliff@usgs.gov>

Date/Publication 2023-01-25 18:40:02 UTC

Repository <https://collincr-usgs.r-universe.dev>

RemoteUrl <https://github.com/cran/gravmagsubs>

RemoteRef HEAD

RemoteSha e8fad99a57b9ca846cb9f2d7f829072b2d9d3983

Contents

gravmagsubs-package	2
rectprismgrav	2
rectprismmag	4

Index	7
--------------	----------

gravmagsubs-package	<i>Gravitational and magnetic attraction of 3-D vertical rectangular prisms</i>
---------------------	---

Description

The package gravmagsubs provides tools for computing the gravitational and magnetic anomalies generated by 3-D vertical rectangular prisms at specific observation points. The package consists of two functions:

- `rectprismgrav` : Computes the gravitational attraction of 3-D right rectangular prisms.
- `rectprismmag` : Computes the magnetic effect of 3-D right rectangular prisms.

Each function can compute the total anomaly of a series of N prisms at M observation points.

Each function also has a logical flag `bycell` (default FALSE). If `bycell=TRUE`, the function returns the contribution from each individual prism.

References

- Plouff, D., 1976, Gravity and magnetic fields of polygonal prisms and application to magnetic terrain corrections, *Geophysics*, v. 41, pp. 727–741, [doi:10.1190/1.1440645](https://doi.org/10.1190/1.1440645).

rectprismgrav	<i>rectprismgrav</i>
---------------	----------------------

Description

Calculates the gravitational attraction of 3-D rectangular prisms. Calculates anomalies of N prisms at M observation stations.

Stations cannot be positioned on the edge of a prism.

Coordinates of stations and prisms are assumed to share a common coordinate system.

Usage

```
rectprismgrav(xstation, ystation, zstation, xmin, xmax, ymin, ymax,
              zdeep, zshallow, deltarho, bycell=FALSE)
```

Arguments

xstation	vector of length M with the x-coordinates of each station, in km, positive east;
ystation	vector of length M with the y-coordinates of each station, in km, positive north;
zstation	vector of length M with the z-coordinates of each station, in km, positive up;
xmin	vector of length N with the minimum x-coordinates of each prism, in km, positive east;
xmax	vector of length N with the maximum x-coordinates of each prism, in km, positive east;
ymin	vector of length N with the minimum y-coordinates of each prism, in km, positive north;
ymax	vector of length N with the maximum y-coordinates of each prism, in km, positive north;
zdeep	vector of length N with the bottom z-coordinates of each prism, in km, positive up;
zshallow	vector of length N with the top z-coordinates of each prism, in km, positive up;
deltarho	vector of length N with the density contrast of each prism, in grams per cubic centimeter (g/cc);
bycell	returns M-by-N matrix with anomaly values generated by individual prisms (default FALSE).

Value

Returns a matrix of length M rows.

If bycell=FALSE, there will be M rows and 1 column, and the element in the i-th row represents the total gravity anomaly generated by all N prisms as observed at the i-th station.

If bycell=TRUE, the matrix will have M rows and N columns, with the element [i, j] representing the anomaly value generated by the j-th prism as observed at the i-th station.

References

- Plouff, D., 1975, Derivation of formulas and FORTRAN programs to compute gravity anomalies of prisms, National Technical Information Service No. PB-243-526, U.S. Department of Commerce, Springfield, VA.
<https://ntrl.ntis.gov/NTRL/dashboard/searchResults/titleDetail/PB243526.xhtml>.

See Also

[rectprismmag](#), [gravmagsubs](#).

Examples

```
#####
## gravity anomaly of a single prism at a single point ##

# location of the point where the gravity anomaly will be calculated
```

```

gravstation <- data.frame(x=0, y=0, z=0)

# the rectangular prism is defined by its six edges
prism1 <- data.frame(xmin=-5, xmax=5,
                    ymin=-5, ymax=5,
                    zmin=-10, zmax=-5)

# density contrast in g/cc
drho <- 0.3

gravanom <- rectprismgrav(gravstation$x, gravstation$y, gravstation$z,
                        prism1$xmin, prism1$xmax,
                        prism1$ymin, prism1$ymax,
                        prism1$zmin, prism1$zmax, drho)

#####

```

rectprismmag

rectprismmag

Description

Calculates the magnetic effect of 3-D rectangular prisms. Calculates anomalies of N prisms at M observation stations.

Stations cannot be positioned inside a prism, or on its edges or faces. Stations cannot be positioned directly below the corners of a prism.

Coordinates of stations and prisms are assumed to share a common coordinate system.

Returns total field magnetic anomaly in nanoteslas (nT).

N.B. Demagnetization effects are ignored in this subroutine.

Usage

```

rectprismmag(xstation, ystation, zstation, xmin, xmax, ymin, ymax,
            zdeep, zshallow, suscvolssi, nrmstr, nrmincl, nrmdecl,
            fieldtotal, fieldincl, fielddecl, bycell=FALSE)

```

Arguments

xstation	vector of length M with the x-coordinates of each station, in km, positive east;
ystation	vector of length M with the y-coordinates of each station, in km, positive north;
zstation	vector of length M with the z-coordinates of each station, in km, positive up;
xmin	vector of length N with the minimum x-coordinates of each prism, in km, positive east;
xmax	vector of length N with the maximum x-coordinates of each prism, in km, positive east;

ymin	vector of length N with the minimum y-coordinates of each prism, in km, positive north;
ymax	vector of length N with the maximum y-coordinates of each prism, in km, positive north;
zdeep	vector of length N with the bottom z-coordinates of each prism, in km, positive up;
zshallow	vector of length N with the top z-coordinates of each prism, in km, positive up;
suscvolsci	vector of length N with the volume susceptibility (unitless);
nrmstr	vector of length N with the remanent magnetization of each prism, in Amperes per meter (A/m);
nrmincl	vector of length N with the inclination angle of the remanent magnetization for each prism, in degrees, positive below horizontal;
nrmdecl	vector of length N with the declination angle of the remanent magnetization for each prism, in degrees, positive east of true north;
fieldtotal	vector of length N with the Earth's field intensity at each prism, in nanoteslas (nT);
fieldincl	vector of length N with the Earth's field inclination at each prism, in degrees, positive below horizontal;
fielddecl	vector of length N with the Earth's field declination at each prism, in degrees, positive east of true north;
bycell	returns M-by-N matrix with anomaly values generated by individual prisms (default FALSE).

Value

Returns a matrix of length M rows.

If `bycell=FALSE`, there will be M rows and 1 column, and the element in the *i*-th row represents the total magnetic anomaly generated by all N prisms as observed at the *i*-th station.

If `bycell=TRUE`, the matrix will have M rows and N columns, with the element `[i, j]` representing the anomaly value generated by the *j*-th prism as observed at the *i*-th station.

References

- Plouff, D., 1975, Derivation of formulas and FORTRAN programs to compute magnetic anomalies of prisms, National Technical Information Service No. PB-243-525, U.S. Department of Commerce, Springfield, VA.
<https://ntrl.ntis.gov/NTRL/dashboard/searchResults/titleDetail/PB243525.xhtml>.

See Also

[rectprismgrav](#), [gravmagsubs](#).

Examples

```
#####
## magnetic anomaly of single prism at a single point ##

# location of the point where the magnetic anomaly will be calculated
magstation <- data.frame(x=0, y=0, z=0)

# the rectangular prism is defined by its six edges
prism1 <- data.frame(xmin=-5, xmax=5,
                    ymin=-5, ymax=5,
                    zmin=-10, zmax=-5)

susc <- 5      # susceptibility (SI)
mstr <- 0      # remanent magnetization (A/m)
mincl <- 0     # remanent inclination (deg)
mdecl <- 0     # remanent declination (deg)
ftotal <- 48800 # Earth's field intensity (nT)
fincl <- 60    # field inclination (deg)
fdecl <- 12    # field declination (deg)

maganom <- rectprismmag(magstation$x, magstation$y, magstation$z,
                       prism1$xmin, prism1$xmax,
                       prism1$ymin, prism1$ymax,
                       prism1$zmin, prism1$zmax, susc,
                       mstr, mincl, mdecl,
                       ftotal, fincl, fdecl)

#####
```

Index

gravmagsubs, [3](#), [5](#)
gravmagsubs (gravmagsubs-package), [2](#)
gravmagsubs-package, [2](#)

rectprismgrav, [2](#), [2](#), [5](#)
rectprismmag, [2](#), [3](#), [4](#)